SERENE

by Pool

Saltwater chlorinator

- + pH regulator
- + ORP controller S4

A complete treatment your way to peace of mind





Bluetooth remote control with e-Pool® application





Premium warranties

Up to 200m³

I TA ALL









Advanced features

• Smart Power technology Constant chlorine production in any circumstances A technology which extends the lifespan of the cell

- Smart pH regulation

 Automatic injection of correcting agent, acid or base
- Controls chlorine production thanks to ORP probe
- Remote control via Bluetooth
 Remote control and update with the e-Pool® application
- Normal Salt/Low Salt mode (depending on model)
- Superboost mode
 Super chlorination for up to 48 hours to overcome an increased need of disinfectant
- Cover mode
 Modulate chlorine production according to cover position
- Self-diagnosis
 Electrolysis test to check the condition of the components
- Automatic winterization
 Automatic winterization and restart from 15°C
- Safeties
 Low water, low salt, cell fault, pH setpoint overrun and overfeeding, high and low ORP value

Easy installation with accessories holder



- Easy integration for all types of installation
- Adaptable to all standards of piping
- Transparent accessories holder

High quality pH and ORP probes



- pH Blue probe factory tested and calibrated
- Accurate pH measurement
- Membrane protection lug
- 2 years warranty







- Self cleaning cell by adjustable polarity inversion
- High quality titanium electrodes 10.000 hours*
- Transparent sleeve to easily check the condition of the plates



- ORP Gold probe for more reliable measurement
- Optimize the lifespan of your equipment
- 1 year warranty

| MODEL | VOLUME m³ | CHLORINE PRODUCTION g/h | REFERENCE |
|----------------------|-----------------|-------------------------|-------------------|
| SERENE S4 Pro 8-40 | 40 | 8 | ELPO22SERA-G4NM08 |
| SERENE S4 Pro 12-60 | 60 | 12 | ELPO22SERA-G4NM12 |
| SERENE S4 Pro 18-90 | NS 90 / LS 60 | NS 18 / LS 13 | ELPO22SERA-G4HX18 |
| SERENE S4 Pro 25-130 | NS 130 / LS 80 | NS 25 / LS 16 | ELPO22SERA-G4HX25 |
| SERENE S4 Pro 40-200 | NS 200 / LS 140 | NS 40 / LS 30 | ELPO22SERA-G4HX40 |