

INVERTER SWIMMING POOL HEAT PUMP

Nero i-ForceLine NEO 24

RATED VOLTAGE/FREQUENCY	220-240V~/50Hz
MOISTURE RESISTANCE	IPX4
ELECTRICAL SHOCKPROOF	I
HEATING CAPACITY(A)	4.7~24.0kW
HEATING POWER INPUT(A)	0.36~4.0kW
COP(A)	13.0~6.0
HEATING CAPACITY(B)	4.40~18.5kW
HEATING POWER INPUT(B)	0.611~4.021kW
COP(B)	7.20~4.60
*RATED POWER INPUT	4.960kW
*RATED CURRENT INPUT	22.5A
WATER VOLUME	10.0m ³ /h
NOISE	44-53dB(A)
NET WEIGHT	92kg
REFRIGERANT/ PROPER INPUT	R32/1.15kg
OPERATION PRESSURE(LOW SIDE)	2.1MPa
OPERATION PRESSURE(HIGHT SIDE)	4.4MPa
MAXIMUM ALLOWABLE PRESSURE	4.4MPa
FACTORY NUMBER(ON THE BAR CODE)	
MANUFACTURED DATE(ON THE BAR CODE)	
A: Outdoor air 27°C/24.3°C; Inlet water 26°C	
B: Outdoor air 15°C/12°C; Inlet water 26°C	
* According to IEC/EN 60335-1	



TermoPool d.o.o.
Ljubiše Miodragovića 11n, Beograd

